

LEAD
THE
FIELD.

XT GrainCarts



Overdeliver.

The all-new XT GrainCart from Brandt delivers industry-leading auger reach for easy positioning and clear visibility that allows you to move more grain, faster.

① Productivity

These carts are designed for quick turnaround and smooth, intuitive in-field operation:

- Industry-leading auger reach delivers the ultimate in operator unload visibility.
- Low-profile tank and tarp design reduces height and delivers maximum combine auger clearance.
- Steep tank angles deliver quick, complete tank cleanout every unload cycle.

② Unrivalled Uptime

XT Series GrainCarts are built with reliable components for long-term dependability:

- Dependable straight-auger design delivers superior reliability and performance.
- Anti-shock auger coupler extends gearbox and driveline lifespan.
- Cushioned auger-fold cylinders are purpose-built for extended auger-fold cycling.

③ Low Operating Cost

Leading performance, reliability, and resale value make the XT GrainCart a solid investment:

- The modular frame and tank design allows for strong, easily-replaceable components.
- Brandt's rugged powder coat paint process optimizes tank cleanout, rust protection, component life, and resale value.
- Half-inch-thick extended-life flighting provides unmatched auger durability.

Powerful Value. **Delivered.**

Brandt

XT GRAINCARTS

SPECIFICATIONS

	1520XT	1320XT	1120XT	1020XT	820XT
Performance					
Capacity (bushels)	1500	1300	1100	1000	850
Unload Speed (bu/min)	600	600	600	600	600
Minimum Horsepower	300	250	200	200	200
General					
Auger Diameter	20"	20"	20"	20"	20"
Flighting	1/2" Extended Life	1/2" Extended Life	1/2" Extended Life	1/2" Extended Life	1/2" Extended Life
Dimensions					
Auger Forward Reach (ahead of hitch)	8'3"	8'3"	8'3"	8'3"	8'3"
Auger Upward Reach (bottom of spout)	13'2"	13'2"	13'2"	13'2"	13'2"
Auger Side Reach (hitch to spout)	15'8"	15'8"	15'8"	15'8"	15'8"
Loading Side Height	11'8"	11'1"	11'3.5"	10'10"	11'
Transport Height	13'1"	12'6"	12'10.5"	12'5"	12'
Overall Height (with auger extended)	18'3"	18'3"	18'3"	18'3"	18'3"
Overall Length	32'4"	32'4"	31'9"	31'9"	31'9"
Width (varies by undercarriage)	13'-15'6"	13'-15'6"	12'10"-16'3.5"	12'10"-16'3.5"	12'10"-16'3.5"
Undercarriage					
Options	Tracks/Tires	Tracks/Tires	Rigid Axle Tires Adjustable Axle Tracks/Tires	Rigid Axle Tires Adjustable Axle Tracks/Tires	Rigid Axle Tires Adjustable Axle Tracks/Tires

FEATURES

Twenty-inch double-pitch auger

double-pitched lower flighting allows an unload capacity of up to 600 bu/min.

Standard four-direction spout

lets you direct grain flow without moving the cart.

Tough driveline & gearbox

ensures that the gearbox input shaft receives steady power, free of any wobble.

Exclusive ground-level access hatch

allows operators to easily enter the grain cart tank from the ground-level while eliminating any chance of leakage.

Robust five-point load bar system

delivers the most accurate and durable load-cell structure on the market.


Brandt Advanced Paint Protection

looks better, lasts longer, and is now available in blue, green, or red to match your other equipment.

Options to fit your needs

including joystick control kit, auto-locking auger fold valve, LED flowgate position indicator, fire suppression kit, hydraulic jack stand, and front-mount tank viewing ladder.



 Now available in red.

For more information
Call us at 1-866-4-BRANDT
Email us at agriculture@brandt.ca
Or visit us at www.brandt.ca

Brandt Agricultural Products
PO Box 317, 13th Avenue & Pinkie Road,
Regina, SK, Canada
S4P 3A1